

Specification Summary

Company Name

ABN:	12345678901	Phone:	07 1234 5678
Postal Address:	PO Box 123 CompanyTown Qld 4000	Fax:	07 1234 5679
		Mobile:	0414 123 456
		E-Mail:	sales@companyname.com.au
		Web:	www.companyname.com.au

Job #: 123
Date: 30/1/2007

Client: **Robert Anderson**
Postal Address: 44 Alton Drive
Wandoah Qld 4988
Phone: 07 4321 5678
Fax: 07 4321 5679
Mobile:
E-Mail:



Site Address: 44 Alton Drive
Wandoah Qld 4988

Wind Rating:	N3	Roof Sheeting	Type
Building Type:	RD Series Shed	Roof Screw	Trimdek
Roof Type:	Gable	Wall Sheeting	12x45 Roof Screw + Seal
Roof Pitch Angle:	10	Wall Screw	Multiclad
Bay size:	3000	Framing Screw	10x16 Sheeting Screw
Bays:	2	Mullion	12x20mm
Length:	6000mm		C15012
Span:	6000mm		
Height:	3000mm		
Apex Height:	3529mm		

	Type	Quantity	Height	Width
Window	Clear Window	1	900	1210
Roller Door	Domestic Series A	1	2600	3430

Roller Door Supplier: Steel-line
Compliance Number: M/405/1B

	Type	Positioning
Roof Purlin	TS6175	Purlins at: 130mm, 1102mm, 2074mm from apex
Wall Girt	TS6175	Girts at: 160mm, 1107mm, 2054mm from slab

	Column	Rafter
Sheeted Frame	C15012	C15012
Unsheeted Frame	C15019	C15019

Base Plate: U Bracket 3mm
Base Plate Anchor: 12x130mm Dynabolt

	Diameter	Depth (including slab)
Minimum shed footing with slab	350mm	750mm
Minimum shed footing without slab	450mm	750mm

This document is produced by ShedPro software as a summary of values, please verify all specifications against certified engineering prior to construction.
For certified shed engineering information, refer to accompanying Sheds Online span table and drawing number 212386-10 sheets 1, 2, 3 & 4.